

0088.32

Bearing EP Grease

NLGI 2

Multipurpose grease thickened with a lithium soap. It possesses good EP, anti-wear, anti-oxidative, anti-corrosion properties and mechanical resistance.

Suitable for several uses in earth moving, agricultural and industrial sectors.

PAKELO BEARING EP GREASE NLGI 2 is a multipurpose grease thickened with lithium soap. Manufacturing process and particular additives confer to the product superior properties if compared to common lithium based greases.

It is formulated with highly solvent refined mineral base oils and special Extreme Pressure (EP), anti-wear, anti-oxidative, anti-rust and anti-corrosion additives.

PAKELO BEARING EP GREASE NLGI 2 shows the following properties:

- excellent anti-wear and Extreme Pressure performance;
- good shear stability even under high mechanical stress;
- good lubricating properties;
- excellent protection against oxidation, rust and corrosion;
- good resistance to hot and cold water washout;
- good pumpability also in centralized lubrication systems requiring NLGI 2 consistency greases.
- recommended for working temperatures between -20°C and +125°C: by shortening greasing drain intervals the product can work even with peaks up to 140°C.

0088.32

Bearing EP Grease

NLGI 2

Application fields

PAKELO BEARING EP GREASE NLGI 2 is a multipurpose grease suitable for several uses in automotive, earth moving, agricultural and industrial sectors (in particular heavy duty equipment lubrication in steel, iron and mining industries).

PAKELO BEARING EP GREASE NLGI 2, thanks to its high mechanical stability and excellent EP properties, is particularly recommended for every kind of rolling and plain bearings and also for heavy-loaded bearings subject to vibrations. It can be used with presence of warm environment in case of not very high working temperatures.

The easy pumpability allows the use the product in centralized lubrication systems requiring NLGI 2 consistency greases.

Performance levels

ISO 6743-9 L-XBCEB 2, DIN 51502 KP2K-20

Chemical-Physical Characteristics

Bearing EP Grease	Method analysis	Unit measure	Value NLGI 2
Colour	-	-	brown
Appearance	-	-	smooth
Thickener	-	-	lithium
NLGI grade	ASTM D217	-	2
Worked Penetration 60 strokes at 25°C	ASTM D217	0,1 mm	280
Worked Penetration 10.000 strokes at 25°C	ASTM D217	0,1 mm	280 (+/-10)
Dropping Point	ASTM D566	°C	190
Copper Corrosion Test (24 hours at 80°C)	ASTM D4048	rating	1b
4 Ball EP Test - Welding Load (10s, 1800rpm)	ASTM D2596	kgf	250
Oil separation during storage (168h at 40°C)	DIN 51817	% (w/w)	3
Recommended Working Temperatures	-	°C	-20 / +125

The data just above refer to average values and must not be understood as guaranteed characteristics.

This Technical Data Sheet has been carefully checked to guarantee complete and precise information. However, we do not take any responsibility in case of damages caused by any mistakes or omissions. Due to continual product research and development, the information contained herein is subject to change without notification.